

Anker SOLIX Smart Meter Gen 2



PN	AE1X0	
SKU	AE1X0310	AE1X0311
Product Name	Anker SOLIX Smart Meter Gen 2 (Single-Phase)	Anker SOLIX Smart Meter Gen 2 (Three-Phase)
Applicability	Anker SOLIX XE AC Anker SOLIX Solarbank Max AC Anker SOLIX Solarbank 4 E5000 Pro	
Product Spec		
Voltage	230 Va.c.	3~230/400 Va.c.
Frequency	50 / 60 Hz	
Accuracy	±1 %	
Max Measurement per Channel	120 A	
Compatible CT	63 A CT(ø 10 mm) 120 A CT(ø 16 mm)	
Communication	RS485; Bluetooth; Wi-Fi (2.4G)	
Operating Temperature	-25°C to 55°C	
Max. Altitude	2,000 m	
Operating Humidity (RH)	5% to 95%	
Power Consumption	< 2 W	
Conductor Stripped Length	9 mm	
Conductor Cross Section	0.5 to 2.5 mm²	
Mounting	DIN Rail 35 mm	
Ingress Protection	IP20 (Indoors Only)	
Warranty	2 Years	
Transportation		
Product Weight	80 g	85 g
Packaging Weight	370 g	450 g
Product Dimensions	105 × 66.7 × 19 mm	105 × 66.7 × 19 mm
Packaging Dimensions	154 × 133 × 69 mm	154 × 133 × 69 mm

Note: The parameters are for the current version and are subject to change upon final release.