





AQUATHERMICA PRO WITHOUT A HEAT EXCHANGER

AQUATHERMICA PRO 200



SAP код	306209
Capacity	202 L
Height	1621 m
Energy class	A+
Maximum operational temperature	75 °C
Maximum working pressure	8 bar
Diameter	630 mm
Heating time	7:24 h:min





Declared load profile	L
Electric heating element power	1.5 kW
Min. ÷ max temperature heat pump air intake (90% R.H.)	-7 ÷ 43 °C
Frequency	50 Hz
Annual electricity consumption in kWh under average climate conditions	702 kWh
Power supply	1/N/220-240 V
Compressor	Rotary
Min. ÷ max temperature installation site	-4 ÷ 40 °C
Compressor protection	Thermal circuit breaker with automatic reset
Maximum current in HP	2.5 + 6.5 (e-heater) = 9 A
Required overload protections	16A T fuse/ 16 A automatic switch characteristic C (to be expected during installation on power supply systems)
Fan	Centrifugal
HP Maximum settable temperature	65 °C
Internal protection	Single safety thermostat with manual reset on a resistive element
Nominal air capacity	360 m ³ /h
Motor protection	Internal thermal circuit breaker with automatic reset
Condenser	Wrapped externally not in contact with water
Transport weight	96.3 kg
Automatic anti-Legionnella disinfection cycle	YES
Defrosting	Active with 4-way valve
CoP (DHW)	3.6





Degree of Protection	IPX4
Refrigerant	R290
Refrigerant charge	150 g
Average heat pump consumption [Condition EN16147:2017 A7/W55]	0.47 kW



Information

AquaThermica Pro 200

Inspired by nature. Powered by technology

TESY AquaThermica Pro is a floor standing air-to-water heat pump for domestic hot water engineered for high energy efficiency, smart performance, and eco-conscious operation. Designed for domestic hot water production, it is available in 200L and 260L capacities

Using the natural R290 (propane) refrigerant, AquaThermica Pro achieves ultra-low Global Warming Potential (GWP) and zero Ozone Depletion Potential (ODP). It can heat water up to 65°C using only the heat pump, offering up to 75% energy savings versus conventional electric water heaters. Its high Coefficient of Performance (COP)—up to 3.8—makes it one of the most efficient systems in its class.

- ° Floor-standing "air-water" heat pump for domestic hot water production.
- ° The AquaThermica Pro range includes models with a volume of 200 and 260 liters without a heat exchanger
- ^o Greater energy efficiency and performance = > ecofriendly refrigerant **R290** /propane/
- $^{\circ}$ Electric heater for faster heating and reaching a high temperature of 75°C
- $^{\circ}\,$ Automatic "Antilegionella" function and self-diagnosis system
- ^o Energy class A+
- ° Reduced CO2 emissions
- $^\circ\,$ Temperature range of the incoming air from -7°C to +43°C
- ^o **Up to 75%** reduced electricity consumption
- ^o Lateral 45° air ducts for installation in rooms as low as 2 meters
- ° Quiet operation: just 34 dB(A) at 1 meter
- ^o **DRY CHECK** Check the magnesuim anode without draining the water.
- ^o **Electronic Expansion Valve (EEV**) for precision refrigerant control
- ^o Microchannel condenser and dual temperature sensors for performance and efficiency
- ^o Connection to solar and photovoltaic panels
- ° Easy-to-use electronic panel

Serie information

AquaThermica Pro 200





Inspired by nature. Powered by technology

TESY AquaThermica Pro is a floor standing air-to-water heat pump for domestic hot water engineered for high energy efficiency, smart performance, and eco-conscious operation.

Using the natural R290 (propane) refrigerant, AquaThermica Pro achieves ultra-low Global Warming Potential (GWP) and zero Ozone Depletion Potential (ODP). It can heat water up to 65°C using only the heat pump, offering up to 75% energy savings versus conventional electric water heaters. Its high Coefficient of Performance (COP)—up to 3.8—makes it one of the most efficient systems in its class.

Key Features:

- Eco friendly refrigerant R290 /propane/
- Lateral 45° air ducts for installation in rooms as low as 2 meters
- Quiet operation: just 34 dB(A) at 1 meter
- Electronic Expansion Valve (EEV) for precision refrigerant control
- Microchannel condenser and dual temperature sensors for performance and efficiency
- Smart operation modes: Boost, Eco, Intelligent, Vacation, High-Demand
- Anti-legionella function, Dry Check MG anode, and modular service design
- Solar and PV panel compatibility

Compact, quiet, and eco-friendly, AquaThermica Pro is the ideal solution for modern homes looking to combine comfort, sustainability, and long-term savings.